

**SECTION 1: IDENTIFICATION****Product Identifier****Product Form:** Mixture**Product Name:** SOLVENT 665**Intended Use of the Product****Use of the Substance/Mixture:** No use is specified.**Name, Address, and Telephone of the Responsible Party****Company**

Helmitin Inc.

99 Shorncliffe Rd

Toronto, Ontario, M8Z 5K7

877.823.2624

11110 Airport Road

Olive Branch, MS 38654

Phone: 877.823.2624

www.helmitin.com

**Emergency Telephone Number****Emergency Number** : CANUTEC 613-996-6666 / CHEMTREC 1-800-424-9300**SECTION 2: HAZARDS IDENTIFICATION****Classification of the Substance or Mixture****Classification (GHS-US)**

Flam. Liq. 2 H225

Skin Irrit. 2 H315

Muta. 1B H340

Repr. 2 H361

STOT SE 3 H336

STOT RE 2 H373

Asp. Tox. 1 H304

Full text of H-phrases: see section 16

**Label Elements****GHS-US Labeling****Hazard Pictograms (GHS-US)****Signal Word (GHS-US)**

: Danger

**Hazard Statements (GHS-US)**: H225 - Highly flammable liquid and vapor.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H336 - May cause drowsiness or dizziness.  
H340 - May cause genetic defects.  
H361 - Suspected of damaging fertility or the unborn child.  
H373 - May cause damage to organs through prolonged or repeated exposure.**Precautionary Statements (GHS-US)**: P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
P240 - Ground/bond container and receiving equipment.  
P241 - Use explosion-proof electrical, ventilating, and lighting equipment.  
P242 - Use only non-sparking tools.

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P243 - Take precautionary measures against static discharge.  
P260 - Do not breathe vapors, mist, or spray.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P280 - Wear respiratory protection, protective gloves, protective clothing, face protection, eye protection.  
P301+P310 - IF SWALLOWED: Immediately call a poison center or doctor.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P331 - Do NOT induce vomiting.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

### Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Flammable vapors can accumulate in head space of closed systems.

**Unknown Acute Toxicity (GHS-US)** Not available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### Mixture

Name	Product Identifier	% (w/w)
Toluene	(CAS No) 108-88-3	30 - 60
Naphtha, petroleum, hydrotreated light*	(CAS No) 64742-49-0	15 - 40
Heptane, branched, cyclic and linear	(CAS No) 426260-76-6	10 - 30
n-Heptane	(CAS No) 142-82-5	3 - 7
Acetone	(CAS No) 67-64-1	1 - 5
Methyl ethyl ketone	(CAS No) 78-93-3	1 - 5

\*Note: Naphtha, petroleum, hydrotreated light, CAS# 64742-49-0 contains n-Hexane CAS# 110-54-3 (45-60%).

## SECTION 4: FIRST AID MEASURES

### Description of First Aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

**Skin Contact:** Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

**Eye Contact:** Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if redness, pain, or irritation occurs.

**Ingestion:** Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### Most Important Symptoms and Effects Both Acute and Delayed

**General:** May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness and dizziness. May cause genetic defects. Suspected of damaging fertility. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.

**Inhalation:** May cause drowsiness or dizziness. Peripheral neurotoxicity has been reported in connection with over exposure to n-hexane. Prolonged exposure over a period of weeks or months to levels well above the TLV may cause neurotoxic disease, with symptoms including weakness and lack of sensation in fingers, hands, arms, feet and legs. Methyl ethyl ketone has been reported to potentiate the neurotoxic effects caused by either n-hexane or methyl-n-butyl ketone. Methyl ethyl ketone by itself does not cause a peripheral neuropathy. MEK may also potentiate the liver and kidney toxicity of haloalkane solvents.

**Skin Contact:** Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Eye Contact:** May cause eye irritation.

**Ingestion:** May be fatal if swallowed and enters airways.

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Chronic Symptoms:** May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. May cause genetic defects.

### **Indication of Any Immediate Medical Attention and Special Treatment Needed**

If you feel unwell, seek medical advice (show the label where possible).

## **SECTION 5: FIRE-FIGHTING MEASURES**

### **Extinguishing Media**

**Suitable Extinguishing Media:** Water spray, fog, carbon dioxide (CO<sub>2</sub>), alcohol-resistant foam, dry chemical, or sand.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### **Special Hazards Arising From the Substance or Mixture**

**Fire Hazard:** Highly flammable liquid and vapor.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

**Reactivity:** Reacts with (strong) oxidizers: (increased) risk of fire. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

### **Advice for Firefighters**

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Hazardous Combustion Products:** Burning can produce carbon monoxide, carbon dioxide, chloride and hydrocarbons. Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. . May release poisonous hydrogen sulfide. Sulfur oxides.

**Other Information:** Refer to Section 9 for flammability properties.

### **Reference to Other Sections**

Refer to section 9 for flammability properties.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **Personal Precautions, Protective Equipment and Emergency Procedures**

**General Measures:** Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray). Use special care to avoid static electric charges. Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

### **For Non-Emergency Personnel**

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

### **For Emergency Personnel**

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

### **Environmental Precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### **Methods and Material for Containment and Cleaning Up**

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Use only non-sparking tools.

### **Reference to Other Sections**

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

## **SECTION 7: HANDLING AND STORAGE**

### **Precautions for Safe Handling**

**Additional Hazards When Processed:** Flammable vapors may accumulate in the head space of closed systems. Container may remain hazardous when empty. Handle empty containers with care because residual vapors are flammable.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. Use only non-sparking tools.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Attacks some forms of plastics, rubber, and coatings.

### Specific End Use(s)

No use is specified.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

<b>Toluene (108-88-3)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	20 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	200 ppm
<b>USA OSHA</b>	OSHA PEL (Ceiling) (ppm)	300 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	100 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	150 ppm
<b>USA IDLH</b>	US IDLH (ppm)	500 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	50 ppm
<b>British Columbia</b>	OEL TWA (ppm)	20 ppm
<b>Manitoba</b>	OEL TWA (ppm)	20 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	50 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	20 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	20 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	150 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	100 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	150 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	100 ppm
<b>Ontario</b>	OEL TWA (ppm)	20 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	20 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	188 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	50 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	60 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	50 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	150 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	100 ppm
<b>n-Heptane (142-82-5)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	400 ppm

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>USA ACGIH</b>	ACGIH STEL (ppm)	500 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2000 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	500 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	85 ppm
<b>USA NIOSH</b>	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (ceiling) (ppm)	440 ppm
<b>USA IDLH</b>	US IDLH (ppm)	750 ppm
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	2050 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	500 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	400 ppm
<b>British Columbia</b>	OEL STEL (ppm)	500 ppm
<b>British Columbia</b>	OEL TWA (ppm)	400 ppm
<b>Manitoba</b>	OEL STEL (ppm)	500 ppm
<b>Manitoba</b>	OEL TWA (ppm)	400 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	2050 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	500 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	400 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	500 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	400 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	500 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	400 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	2049 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	500 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	400 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	2049 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	500 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	400 ppm
<b>Ontario</b>	OEL STEL (ppm)	500 ppm
<b>Ontario</b>	OEL TWA (ppm)	400 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	500 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	400 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	2050 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	500 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	1640 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	400 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	500 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	400 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	2000 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	500 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	1600 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	400 ppm
<b>Acetone (67-64-1)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	500 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	750 ppm
<b>USA ACGIH</b>	ACGIH chemical category	Not Classifiable as a Human Carcinogen
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	1000 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	250 ppm
<b>USA IDLH</b>	US IDLH (ppm)	2500 ppm (10% LEL)
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	750 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	500 ppm
<b>British Columbia</b>	OEL STEL (ppm)	500 ppm
<b>British Columbia</b>	OEL TWA (ppm)	250 ppm
<b>Manitoba</b>	OEL STEL (ppm)	750 ppm
<b>Manitoba</b>	OEL TWA (ppm)	500 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	1782 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	750 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	1188 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	500 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	750 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	500 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	750 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	500 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	2970 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	1250 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	2370 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	1000 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	2970 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	1250 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	2370 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	1000 ppm
<b>Ontario</b>	OEL STEL (ppm)	750 ppm
<b>Ontario</b>	OEL TWA (ppm)	500 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	750 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	500 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	2380 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	1000 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	1190 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	500 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	750 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	500 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	3000 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	1250 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	1000 ppm
<b>Methyl ethyl ketone (78-93-3)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	200 ppm
<b>USA ACGIH</b>	ACGIH STEL (ppm)	300 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	200 ppm
<b>USA NIOSH</b>	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (TWA) (ppm)	200 ppm
<b>USA NIOSH</b>	NIOSH REL (STEL) (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
<b>USA NIOSH</b>	NIOSH REL (STEL) (ppm)	300 ppm

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>USA IDLH</b>	US IDLH (ppm)	3000 ppm
<b>Alberta</b>	OEL STEL (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
<b>Alberta</b>	OEL STEL (ppm)	300 ppm
<b>Alberta</b>	OEL TWA (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>Alberta</b>	OEL TWA (ppm)	200 ppm
<b>British Columbia</b>	OEL STEL (ppm)	100 ppm
<b>British Columbia</b>	OEL TWA (ppm)	50 ppm
<b>Manitoba</b>	OEL STEL (ppm)	300 ppm
<b>Manitoba</b>	OEL TWA (ppm)	200 ppm
<b>New Brunswick</b>	OEL STEL (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL STEL (ppm)	300 ppm
<b>New Brunswick</b>	OEL TWA (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>New Brunswick</b>	OEL TWA (ppm)	200 ppm
<b>Newfoundland &amp; Labrador</b>	OEL STEL (ppm)	300 ppm
<b>Newfoundland &amp; Labrador</b>	OEL TWA (ppm)	200 ppm
<b>Nova Scotia</b>	OEL STEL (ppm)	300 ppm
<b>Nova Scotia</b>	OEL TWA (ppm)	200 ppm
<b>Nunavut</b>	OEL STEL (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL STEL (ppm)	300 ppm
<b>Nunavut</b>	OEL TWA (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>Nunavut</b>	OEL TWA (ppm)	200 ppm
<b>Northwest Territories</b>	OEL STEL (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL STEL (ppm)	300 ppm
<b>Northwest Territories</b>	OEL TWA (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>Northwest Territories</b>	OEL TWA (ppm)	200 ppm
<b>Ontario</b>	OEL STEL (ppm)	300 ppm
<b>Ontario</b>	OEL TWA (ppm)	200 ppm
<b>Prince Edward Island</b>	OEL STEL (ppm)	300 ppm
<b>Prince Edward Island</b>	OEL TWA (ppm)	200 ppm
<b>Québec</b>	VECD (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
<b>Québec</b>	VECD (ppm)	100 ppm
<b>Québec</b>	VEMP (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
<b>Québec</b>	VEMP (ppm)	50 ppm
<b>Saskatchewan</b>	OEL STEL (ppm)	300 ppm
<b>Saskatchewan</b>	OEL TWA (ppm)	200 ppm
<b>Yukon</b>	OEL STEL (mg/m <sup>3</sup> )	740 mg/m <sup>3</sup>
<b>Yukon</b>	OEL STEL (ppm)	250 ppm
<b>Yukon</b>	OEL TWA (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
<b>Yukon</b>	OEL TWA (ppm)	200 ppm
<b>n-Hexane (110-54-3)</b>		
<b>USA ACGIH</b>	ACGIH TWA (ppm)	50 ppm
<b>USA OSHA</b>	OSHA PEL (TWA) (ppm)	500 ppm

### Exposure Controls

**Appropriate Engineering Controls:** Gas detectors should be used when flammable gases/vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Personal Protective Equipment:** Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics.

**Hand Protection:** Wear chemically resistant protective gloves.

**Eye Protection:** Chemical safety goggles.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

**Environmental Exposure Controls:** Do not allow the product to be released into the environment.

**Consumer Exposure Controls:** Do not eat, drink or smoke during use

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on Basic Physical and Chemical Properties

<b>Physical State</b>	: Liquid
<b>Appearance</b>	: Clear, colorless
<b>Odor</b>	: Mild aromatic
<b>Odor Threshold</b>	: Not available
<b>pH</b>	: Not applicable
<b>Evaporation Rate</b>	: $\leq 8.0$ [Ref Std: <i>n</i> -Butyl acetate = 1.0]
<b>Melting Point</b>	: Not available
<b>Freezing Point</b>	: Not available
<b>Boiling Point</b>	: 88 °C (190.40 °F)
<b>Flash Point</b>	: $< -18$ °C (-0.40 °F) (Tag Closed Cup)
<b>Auto-ignition Temperature</b>	: $>203$ °C (397 °F)
<b>Decomposition Temperature</b>	: Not available
<b>Flammability (solid, gas)</b>	: Not available
<b>Lower Flammable Limit</b>	: 1.0 %
<b>Upper Flammable Limit</b>	: 13.0 %
<b>Vapor Pressure</b>	: $\leq 142$ mm Hg @ 20 °C (68 °F)
<b>Relative Vapor Density at 20 °C</b>	: $\geq 2.0$ [Ref Std: Air = 1.0]
<b>Relative Density</b>	: 0.77 g/mL
<b>Specific Gravity</b>	: 0.77 @ 20 °C (68 °F)
<b>Solubility</b>	: Not soluble in water
<b>Partition Coefficient: N-Octanol/Water</b>	: Not available
<b>Viscosity</b>	: Not available
<b>Solids Content</b>	: 0% (completely volatile)
<b>Explosion Data – Sensitivity to Mechanical Impact</b>	: Not expected to present an explosion hazard due to mechanical impact.
<b>Explosion Data – Sensitivity to Static Discharge</b>	: Yes, in certain circumstances product can ignite due to static discharge.
<b>VOC Content (SCAQMD Rule 1168)</b>	: 764 g/L (6.37 lbs/gal)
<b>VHAP Content</b>	: 67% (wt/wt)



# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### SECTION 10: STABILITY AND REACTIVITY

**Reactivity:** Reacts with (strong) oxidizers: (increased) risk of fire. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

**Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

**Incompatible Materials:** Strong acids. Strong bases. Strong oxidizers. Attacks some forms of plastics, rubber, and coatings.

**Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>). Contains Sulfur, may release small amounts of hydrogen sulfide. Hydrogen sulfide is a highly flammable, explosive gas under certain conditions, is a toxic gas, and may be fatal. Gas can accumulate in the headspace of closed containers, use caution when opening sealed containers. Heating the product or containers can cause thermal decomposition of the product and release hydrogen sulfide. Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons.

### SECTION 11: TOXICOLOGICAL INFORMATION

#### Information on Toxicological Effects - Product

**Acute Toxicity:** Not classified

**LD50 and LC50 Data:** Not available

**Skin Corrosion/Irritation:** Causes skin irritation.

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** May cause genetic defects.

**Teratogenicity:** Not classified

**Carcinogenicity:** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** May cause damage to organs through prolonged or repeated exposure.

**Reproductive Toxicity:** Suspected of damaging fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** May cause drowsiness or dizziness.

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** May cause drowsiness or dizziness. Peripheral neurotoxicity has been reported in connection with over exposure to n-hexane. Prolonged exposure over a period of weeks or months to levels well above the TLV may cause neurotoxic disease, with symptoms including weakness and lack of sensation in fingers, hands, arms, feet and legs. Methyl ethyl ketone has been reported to potentiate the neurotoxic effects caused by either n-hexane or methyl-n-butyl ketone. Methyl ethyl ketone by itself does not cause a peripheral neuropathy. MEK may also potentiate the liver and kidney toxicity of haloalkane solvents.

**Symptoms/Injuries After Skin Contact:** Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

**Symptoms/Injuries After Eye Contact:** May cause eye irritation.

**Symptoms/Injuries After Ingestion:** May be fatal if swallowed and enters airways.

**Chronic Symptoms:** May cause damage to organs through prolonged or repeated exposure. Suspected of damaging fertility or the unborn child. May cause genetic defects.

#### Information on Toxicological Effects - Ingredient(s)

##### LD50 and LC50 Data:

<b>Toluene (108-88-3)</b>	
LD50 Oral Rat	5580 mg/kg
LD50 Dermal Rabbit	12000 mg/kg
ATE US (vapors)	25.70 mg/l/4h
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 3160 mg/kg
<b>n-Heptane (142-82-5)</b>	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	3000 mg/kg
LC50 Inhalation Rat	103 g/m <sup>3</sup> (Exposure time: 4 h)

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

<b>Acetone (67-64-1)</b>	
LD50 Oral Rat	5800 mg/kg
LD50 Dermal Rabbit	15688 mg/kg
LC50 Inhalation Rat	44 g/m <sup>3</sup>
<b>Methyl ethyl ketone (78-93-3)</b>	
LD50 Oral Rat	2054 mg/kg
LD50 Dermal Rat	> 10 ml/kg
LD50 Dermal Rabbit	5000 mg/kg
LC50 Inhalation Rat	11700 ppm/4h
<b>Toluene (108-88-3)</b>	
IARC Group	3

## SECTION 12: ECOLOGICAL INFORMATION

### Toxicity

**Ecology - General:** Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

<b>Toluene (108-88-3)</b>	
LC50 Fish 1	15.22 (15.22 - 19.05) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 (5.46 - 9.83) mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
LC50 Fish 1	8.2 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>n-Heptane (142-82-5)</b>	
LC50 Fish 1	375.0 mg/l (Exposure time: 96 h - Species: Cichlid fish)
<b>Acetone (67-64-1)</b>	
LC50 Fish 1	4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC 50 Fish 2	6210 (6210 - 8120) mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 (12600 - 12700) mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Methyl ethyl ketone (78-93-3)</b>	
LC50 Fish 1	3130 (3130 - 3320) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	520 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	5091 mg/l (Exposure time: 48 h - Species: Daphnia magna)

### Persistence and Degradability

<b>Acetone (67-64-1)</b>	
Persistence and Degradability	Readily biodegradable in water.

### Bioaccumulative Potential

<b>Toluene (108-88-3)</b>	
Log Pow	2.65
<b>n-Heptane (142-82-5)</b>	
Log Pow	4.66
<b>Acetone (67-64-1)</b>	
BCF Fish 1	0.69
Log Kow	-0.24
<b>Methyl ethyl ketone (78-93-3)</b>	
Log Pow	0.29

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

**Mobility in Soil** Not available

### **Other Adverse Effects**

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

**Ecology – Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

### **In Accordance with DOT**

**Proper Shipping Name** : PAINT RELATED MATERIAL  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3  
**Packing Group** : II  
**Marine Pollutant** : Marine pollutant  
**ERG Number** : 138



### **In Accordance with TDG**

**Proper Shipping Name** : PAINT RELATED MATERIAL  
**Packing Group** : II  
**Hazard Class** : 3  
**Identification Number** : UN1263  
**Label Codes** : 3  
**Marine Pollutant (TDG)** : Marine pollutant



## SECTION 15: REGULATORY INFORMATION

### **US Federal Regulations**


<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard
<b>Toluene (108-88-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
<b>RQ (Reportable Quantity, Section 304 of EPA's List of Lists):</b>	1000 lb
<b>SARA Section 313 - Emission Reporting</b>	1.0 %
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Heptane, branched, cyclic and linear (426260-76-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>n-Heptane (142-82-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Acetone (67-64-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Methyl ethyl ketone (78-93-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>SARA Section 311/312 Hazard Classes</b>	Immediate (acute) health hazard Fire hazard

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

### US State Regulations

**Proposition 65** –  **WARNING:** This product can expose you to chemicals including **Ethylbenzene (CAS# 100-41-4)** which is known to the State of California to cause cancer, and **Toluene (CAS# 108-88-3)** which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

<b>Toluene (108-88-3)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>n-Heptane (142-82-5)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Acetone (67-64-1)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List
<b>Methyl ethyl ketone (78-93-3)</b> U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

### Canadian Regulations

<b>Toluene (108-88-3)</b> Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List) IDL Concentration 1 %
<b>Naphtha, petroleum, hydrotreated light (64742-49-0)</b> Listed on the Canadian DSL (Domestic Substances List)
<b>Heptane, branched, cyclic and linear (426260-76-6)</b> Listed on the Canadian DSL (Domestic Substances List)
<b>n-Heptane (142-82-5)</b> Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List) IDL Concentration 1 %
<b>Acetone (67-64-1)</b> Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List) IDL Concentration 1 %
<b>Methyl ethyl ketone (78-93-3)</b> Listed on the Canadian DSL (Domestic Substances List) Listed on the Canadian IDL (Ingredient Disclosure List) IDL Concentration 1 %

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

### SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 01/29/2018

# SOLVENT 665

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

---

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**GHS Full Text Phrases:**

H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

North America GHS US 2012 & WHMIS 2